

# SAMURAI V2 SERIES

## SAMURAI 12V/24V ELECTRIC WINCHES



Revolutionary design external brake.

Fully sealed to IP68 Standard.

600 amp silver tip contactors.

Solid Brass Contacts Direct to the Motor.

Laser etched extruded aluminium tie bars.

Silver Copper Motor with Copper Brush Holders

### INCLUDED



12V only



WIRE ROPE AVAILABLE



Our top performance winches just got better! The Next Generation Samurai models are faster, with lower current draw and include a new external brake. Other new features include an updated hook, wired remote and upgraded wireless remote. Comes with stainless steel roller fairlead (or Aluminium fairlead) and fittings as standard and backed by Warrior's un-rivalled Limited Lifetime Warranty. 12v versions come complete with Heavy Duty integrated wireless remote.

### STANDARD ACCESSORIES

- ⊕ Galvanised Steel Cable or Synthetic Rope
- ⊕ 3.8m Remote Handset
- ⊕ Aluminium or Stainless Steel Fairlead
- ⊕ Heavy Duty Battery Leads
- ⊕ Isolation Switch
- ⊕ Stainless Steel Mounting Hardware
- ⊕ Built In Wireless remote (12v only)
- ⊕ Heavy Duty Hook

### OUTSTANDING FEATURES

- ⊕ External Brake.
- ⊕ All Brass (no corrosion) Series Wound Motor
- ⊕ Double Sealed Motor
- ⊕ Sealed Waterproof Contactor
- ⊕ Reinforced Plastic Contactor Cover
- ⊕ Double Sealed Drum (Gearbox/Motor)
- ⊕ Sealed 3 Stage Planetary Gears

### TECHNICAL SPECIFICATIONS

| Model                                  | Line Pull              | Motor (12v)    | Speed (No load) ft (m) p/min | Gearing | Cable (DxL)                           | Size              | Weight                  |
|--|------------------------|----------------|------------------------------|---------|---------------------------------------|-------------------|-------------------------|
| <b>800VS12/24</b><br><b>800VA12/24</b> | 8000 lbs<br>(3636 kg)  | 5.8hp<br>4.3Kw | 33.4 (10.2)                  | 196:1   | 8.3mm x 29m (W)<br>8.3mm x 29m (SR)   | 559 x 160 x 248mm | 32 kg (W)<br>25 kg (SR) |
| <b>950VS12/24</b><br><b>950VA12/24</b> | 9500 lbs<br>(4500 kg)  | 6.1hp<br>4.6kw | 33.4 (10.2)                  | 196:1   | 9.2mm x 26m (W)<br>9.5mm x 25m (SR)   | 559 x 160 x 248mm | 42 kg (W)<br>32 kg (SR) |
| <b>120VS12/24</b><br><b>120VA12/24</b> | 12000 lbs<br>(5400 kg) | 6.5hp<br>4.6kw | 29.5 (9.0)                   | 253:1   | 10.2mm x 26m (W)<br>11mm x 25m (SR)   | 559 x 160 x 248mm | 40 kg (W)<br>30 kg (SR) |
| <b>145VS12/24</b><br><b>145VA12/24</b> | 14500 lbs<br>(6577 kg) | 7.2hp<br>5.4kw | 31.16 (9.5)                  | 253:1   | 10.2mm x 25.5m (W)<br>11mm x 25m (SR) | 593 x 160 x 248mm | 46 kg (W)<br>36 kg (SR) |